

## Communications & Power Industries CCTWT

The VTS-5755 pulsed-coupled cavity TWT covers 2.7 GHz to 3.1 GHz with 60 kW peak output power, up to 2.4% duty cycle. This device has a non-intercepting grid pulsed and single stage depressed collector to achieve 50 dB gain. This device is capable of parallel operation from a common HV power supply, phase tracking is better than +/- 20 degrees. The long life CD coated cathode is capable of pulse width to 50 micro seconds in this PPM focused, air cooled TWT.



Contact us at [MPPMarketing@cpii.com](mailto:MPPMarketing@cpii.com) or call us at +1 650-846-2800.

### FEATURES:

- 2.7 GHz to 3.1 GHz
- 60 kW Peak output power
- Up to 2.4% duty cycle
- Non-intercepting grid pulsed
- 50 dB gain
- Single stage depressed collector
- Forced air cooled
- PPM focused
- Coaxial type-n-input, CPR 284 waveguide output

### BENEFITS:

- Efficient
- Bandwidth
- Over 40 years of technical expertise

### APPLICATIONS:

- Ground radars

### Typical Operating Parameters

PARAMETER	MIN	MAX	UNITS
Cathode Voltage	-33	-30	kV
Cathode Current	8	10	a
Heater Voltage	8	11	V
Heater Current	6	11	A
Collector Voltage	20	22	kV
Grid Bias Voltage	-400	-600	V
Grid Pulse Voltage	350	600	v
RF Drive Power	---	0.5	W
Pulse Width	---	40	µsec
Duty Cycle	---	2.4	%
Air Flow Rate	13	14	Lbs/min
Pressure Drop	---	5	inches
Weight	---	80	lbs
Dimensions	---	12 X15X47	inches