

### CPI Ka-Band TWTA for Satellite Uplink Communications

Provides 100 or 145 watts of CW power in a rugged and compact weatherproof package, digital ready, for wideband single- and multi-carrier satellite service over up to 1.0 GHz within the Ka-band frequency range. Ideal for both transportable and fixed earth station applications.

#### Cost Effective, Efficient, Rugged

Employs a high efficiency helix traveling wave tube, reducing operating costs. Rugged construction allows for operation in extreme environments.

#### Meets Global Requirements

Meets International Safety Standard EN-60215, Electromagnetic Compatibility 2014/30/EU and Harmonic Standard EN-61000-3-2 to satisfy worldwide requirements. CE Marked.

#### Worldwide Support

Backed by over four decades of satellite communications experience, and CPI's worldwide 24-hour customer support network which includes more than 20 regional factory service centers.



CPI Model T01KO-B, 120/175 W Ka-band TWTA, provides up to 145 watts of CW power at the flange

#### OPTIONS:

- Remote control panel
- Integral switch control and drive
- Redundant or power combined subsystems
- Integral linearizer????
- Ethernet interface
- For this amplifier without a BUC, refer to CPI pub. MKT-99
- Integral harmonic filter

Quality Management  
System - ISO 9001:2015



Specification	T01KO-B 175 W CW power	T01KO-B 120 W CW power
Input Frequency	Starting at 950 MHz, 1000 MHz or 1100 MHz, and extending over the width of the output frequency band	
Output Frequency	Up to 1 GHz instantaneous bandwidth within the 27.5 to 31.0 GHz frequency band	
TWT / Flange CW Power	175 W / 145 W	125W / 100 W
Intermodulation - with respect to each of two carriers	-23 dBc @ 4 dB backoff from rated power with optional linearizer	
Noise Power Ratio	18 dB at 4 dB backoff from rated power with optional linearizer	
Spectral Regrowth	30 dB at 4 dB backoff from rated power with optional linearizer	
Gain	70 dB min. with optional linearizer	
RF Level Adjust Range	0 to 25 dB (via PIN diode attenuator) min, 0.1 dB steps	
Gain Stability	±0.25 dB/24 hour max,max. at constant drive and temperature, after 30 minute warmup ±1.0 dB max. over operating temperature range	
Small Signal Gain Slope	±0.04 dB/MHz max.	
Small Signal Gain Variation	1.0 dB pk-pk max. across any 40 MHz segment; 4.5 dB pk-pk max. across 1 GHz segment	
Input/Output VSWR	1.5:1 max. / 1.3:1 max.	
Load VSWR	1.5:1 max. full spec. compliance; 2.0:1 max. continuous; any value for operation without damage;	
Phase Noise	-12 dB below IESS-308 continuous mask; -50 dBc AC fundamental; -47 dBc sum of all spurs	
Spurious	-60 dBc max.	
AM/PM Conversion	1.0°/dB max. up to 3 dB OBO with optional linearizer	
Harmonic Output	-12 dBc max. at rated power (-60 dBc with optional harmonic filter)	
Noise Density	<-150 dBW/4 kHz below 21.2 GHz; <-65 dBW/4 kHz max. in passband	
Group Delay (over 40 MHz)	0.02 ns/MHz linear max; 0.007 ns/MHz <sup>2</sup> parabolic max; 1.0 ns pk-pk ripple max.	
Primary Power	Voltage: Single phase, 100-240 VAC ±10%; Frequency: 47-63 Hz	
Power Consumption	750 VA typ, 800 VAC max.	650 VA typ, 700 VAC max.
Power Factor	0.95 min; 0.99 typ.	
Ambient Temperature	-40°C to +50°C operating in direct sunlight (to +55°C out of direct sunlight); -54°C to +71°C non-operating	
Relative Humidity	100% condensing	
Altitude	10,000 ft. with standard adiabatic derating of 2°C/1000 ft. operating; 50,000 ft. non-operating	
Shock and Vibration	20 G <sub>peak</sub> , 11 ms 1/2 sine; 2.1 g <sub>rms</sub> , 5 to 500 Hz (non-operational)	
Cooling	Forced Air with integral blower	
Connections	RF Input: WR-28F (WR-34F optional); RF output: WR-34G (WR-28G optional); RF output monitor: 2.9mm SMA Female	
M&C Interface	Ethernet (RS422/485 serial optional)	
Dimensions, W x H x D	10.25 x 9.5 x 20.0 inches (261 x 242 x 508 mm)	
Weight	52 lbs (23.6 kg) with no options	
Heat Dissipation	600 W typ.	500 W typ.
Acoustic noise	65 dBA (as measured at 3 ft.) nom.	
Note 1	Customer must select desired frequency range at time of purchase. This decision is TWT dependent and is not field changeable. CW power is reduced by 0.1 dB with harmonic filter option.	



**SMP Division**  
**Satcom Products**  
tel: +1 669-275-2744  
email: [satcommarketing@cpii.com](mailto:satcommarketing@cpii.com)  
web: [www.cpii.com/satcom](http://www.cpii.com/satcom)

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

© 2020 Communications & Power Industries LLC. Company proprietary; use and reproduction is strictly prohibited without written authorization from CPI.