Communications & Power Industries Triode





The 3CX20,000H3 is a forced air cooled, ceramic/metal, medium-mu power triode designed primarily for use in industrial radio frequency heating services. Input of 84 kW is permissible up to 90 MHz. Plentiful reserve emission is available from it's 1600 watt filament. The grid structure is rated at 800 watts making this tube an excellent choice for industrial service.

FEATURES:

Maximum plate dissipation: 20,000 Watts

Maximum screen dissipation: ---

Maximum grid dissipation: 800 Watts
Frequency for max rating (CW): 90 MHz
Amplification factor: 20

Filament/cathode: Thoriated Tungsten

Voltage: 10.0 Volts Current: 160 Amps

Capacitance: Grounded cathode

Input: 70.0 pF
Output: 2.3 pF
Feedthrough: 43.0 pF

Capacitance: Grounded grid

Input: --- pF
Output: --- pF
Feedthrough: --- pF

Cooling: Forced Air

Base: Flexible Filament Leads

Air Socket: --Air Chimney: --Boiler: ---

Length: 19.0 in; 482.6 mm
Diameter: 8.0 in; 203.2 mm
Weight: 20.0 lb; 9.1 kg

BENEFITS:

Worldwide brand name recognitionOver 85 years technical expertise

APPLICATIONS:

- Communications
- Industrial



With a history of producing high quality products, we can help you with your triode.

Contact us at MPPMarketing@cpii.com or call us at +1 650-846-2800. The data should be used for basic information only.

Formal, controlled specifications may be obtained from CPI for use in equipment design.



Microwave Power Products Division 811 Hansen Way Palo Alto, California USA 94304 tel +1 650-846-2800 fax +1 650-856-0705 email MPPMarketing@cpii.com web www.cpii.com/MPP For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

©2020 Communications & Power Industries LLC. Company proprietary: use and reproduction is strictly prohibited without written authorization from CPI.