Communications & Power Industries Triode





The Y-811 is a planar triode intended for use as a high voltage series regulator or switch tube. The compact, low inductance package allows fast rise and fall times and very short pulse operation. The plate is conduction cooled and rated at 1000 watts when used with the proper heatsink. When immersed in oil the maximum plate voltage rating is 65 kV.

FEATURES:

Maximum plate dissipation: 1,000 Watts

Maximum screen dissipation: ---

Maximum grid dissipation: 1.5 Watts
Frequency for max rating (CW): --- MHz
Amplification factor: 950

Filament/cathode: Oxide Coated

Voltage: 6.3 Volts Current: 2.25 Amps

Capacitance: Grounded cathode

Input: 15.0 pF
Output: 0.003 pF
Feedthrough: 2.0 pF

Capacitance: Grounded grid

Input: --- pF
Output: --- pF
Feedthrough: --- pF

Cooling: Conduction
Base: Special

Air Socket: --Air Chimney: --Boiler: ---

 Length:
 2.83 in; 7.175 cm

 Diameter:
 3.01 in; 7.65 cm

 Weight:
 18.34 oz; 520 gm

BENEFITS:

• Worldwide brand name recognition

• Over 85 years technical expertise

APPLICATIONS:

• Science



| | | MAXIMUM RATINGS | | TYPICAL OPERATION | | | | |
|-----------------------|--------------------------------|-----------------------------|----------------------------|-----------------------------|------------------------------|----------------------------|---------------------------|--------------------------------|
| Class of Operation | Type of Service | Plate Voltage (Volts) | Plate Current (Amps) | Plate Voltage (Volts) | Screen Voltage (Volts) | Plate Current (Amps) | Drive Power (Watts) | Output Power (kiloWatts) |
| | Switch Tube or Pulse Modulator | 85,000 | 10 | | | | | |

With a history of producing high quality products, we can help you with your triode.

Contact us at MPPMarketing@cpii.com or call us at +1 650-846-2800. The data should be used for basic information only.

Formal, controlled specifications may be obtained from CPI for use in equipment design.



Microwave Power Products Division 811 Hansen Way Palo Alto, California USA 94304 tel +1 650-846-2800 fax +1 650-856-0705 email MPPMarketing@cpii.com web www.cpii.com/MPP For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

©2020 Communications & Power Industries LLC. Company proprietary: use and reproduction is strictly prohibited without written authorization from CPI.